


COVERINGS ETC

ECO-TERR®

Cut Sheet

Standart



Overview

Embrace quality and style with Eco-TerrR flooring and countertops. Eco-TerrR is a Future-Friendly™ material made of recycled natural stone aggregates.

Durable, zero VOC materials, cleanable finish does not support microbial growth, nor allow

moisture to accumulate, helping to maintain a mold-free environment with improved indoor air quality.

Contains pre-consumer recycled content; may help contribute toward LEED® credits with USGBC project certification.

Specifications

Coefficient of Friction	ASTM C-1028	Polished	Dry: 0.64; Wet: 0.61
		Honed	Dry: 0.71; Wet: 0.68
		Microlinen	Dry: 0.74; Wet: 0.70
Resistance to Fire	ASTM Class 0		
Freeze-Thaw	ASTM C-666	None (300 cycles)	
Compressive Strength	ASTM C-170	14,000 - 28,000 psi	
Modulus of Rupture	ASTM C-99	1,550 psi	
Flexural Strength	ASTM C-880	1,973 psi	
Water Absorption	ASTM C-97	3.2%	

AVAILABLE SIZES

Sheets

16" x 16" x 5/8"

24" x 24" x 3/4"

FINISHES

Honed, Microlinen and Polish.

COLLECTION



* Approximate laboratory test values.
* Colors may not print accurately. Please request sample. Recycled content may cause slight color variation.